





CS Code	Beam Type	Beam angle	Power W	Tension V	Peak intensity cd	avg.life hrs	Color Temp. K	Overall length mm	a mm	Base	Packing
Par64											
C2101	VNSP	12 /9	1000	230	320000	300	3200	204	152.4	GX16d	6
C2102	NSP	14 /10	1000	230	270000	300	3200	204	152.4	GX16d	6
C2103	MFL	24 /11	1000	230	125000	300	3200	204	152.4	GX16d	6
C2100	WFL	-	1000	230	40000	300	3200	204	152.4	GX16d	6
C2051	VNSP	12 /9	500	230	240000	300	3200	204	152.4	GX16d	6
C2052	NSP	14 /10	500	230	140000	300	3200	204	152.4	GX16d	6
C2053	MFL	24 /11	500	230	65000	300	3200	204	152.4	GX16d	6
C2101/1	VNSP	12 /9	1000	120	400000	300	3200	204	152.4	GX16d	6
C2102/1	NSP	14 /10	1000	120	330000	300	3200	204	152.4	GX16d	6
C2103/1	MFL	24 /11	1000	120	125000	300	3200	204	152.4	GX16d	6
C2100/1	WFL	-	1000	120	40000	300	3200	204	152.4	GX16d	6
C2104	VNSP	-	250	28	500000	25	-	204	95	Screw	6



Par56											
C2105/V	VNSP	-	300	230	68000	1000	2800	178	127	Mog End Pr	12
C2105/N	NSP	-	300	230	-	1000	2800	178	127	Mog End Pr	12
C2105/M	MFL	-	300	230	-	1000	2800	178	127	Mog End Pr	12
C2105/W	WFL	-	300	230	-	1000	2800	178	127	Mog End Pr	12
C2106	MFL	-	300	12	6000lm	1000	2800	178	114	Screw	12

Par36											
C2107	VNSP	-	30	6.4	55000	100	3200	114	70	Screw	36
C2108	VNSP	-	30	12.8	50000	100	3200	114	70	Screw	36
C2109	VNSP	-	50	28	45000	400	3200	114	70	Screw	36
C2110	VNSP	-	100	13	110000	25	3200	114	70	Screw	36
C2111	WFL	-	650	120	24000	100	3200	114	70	Screw	36

Alternative codes	
LIF	ANSI
CP60	EXC
CP61	EXD
CP62	EXE
-	EXG
CP86	-
CP87	-
CP88	-
-	FFN
-	FFP
-	FFR
-	FFS
GE:4552	-

LIF	ANSI
-	-
-	-
-	-
-	-

LIF	ANSI
GE:4515	-
GE:4405	-
GE:4505	-
GE:4509	-
GE:DWE	-